

Model 1520-001

Overview

The REVGUARD 2 Speed Switch eliminates the hazard of an overspeed condition. When engine RPMs exceed the Revguard's programmed setpoint, the output is energized, providing the signal to actuate the air intake shutoff valve(s) to shut off your engine.

Revguard 2 is easy to use and install. It is field programmable which allows users the flexibility to customize it to fit their specific needs.

Features and Benefits

- Field programmability
- Electronics are encapsulated for protection from fuel, moisture and dirt
- Built-in test mode for temporarily operating the engine shut off signal at reduced rpm without over revving engine
- Can be connected to optional remote test switch and/or LED indicator light in available kit
- LED light to indicate status
- Output capable of passing up to 4A
- Operates from 12 VDC to 32 VDC
- Operating temperatures of -40°C to 85°C (-22°F to 167°F)
- Screw terminals for easy installation

Testing

- EMC
- EMI/RFI/ESD
- Highly Accelerated Life Test
- Thermal Shock
- Vibration
- Humidity Test
- Salt Spray Test





Trusted Industry Experts


We are the leading provider of air intake shutoff valves and systems with manufacturing facilities in England, Canada and the United States to serve our global markets. Our success is driven by our people and their commitment to exceed customer expectations. We will help you find the right protection system for your diesel engine application.



REVGUARD 2 Speed Switch

Model 1520-001

Dimensions



Specifications

Input Power	Supply voltage	12V - 32 VDC with reverse polarity protection
Input Signal	Frequency range	100 Hz - 10,000 Hz
	Input signal type	Sine wave or square wave
	Setpoint repeatability	Less then 1% deviation
Output Signal	Contact relay	4A max
	Local trip indication	Red LED
Testing	Test function	Reduces setpoints by 10, 20, 30 or 50%
	Activation	Push button w/option for remote testing
Physical Properties	Body material	Plastic, ABS
	Wire terminals	Plated screw terminals
	Operating temperature range	-40°C to 85°C (-22°F to 167°F)
Certification	Ingress protection	IP54

Contact our sales offices below for more information or to find your local distributor, visit our website and select "Find Local Distributor".

Americas

AMOT - USA Tel +1 (281) 940 1800 Fax +1 (713) 559 9419 sales@amot.com

Roda Deaco - Canada Tel +1 (780) 465 4429 Fax +1 (780) 469 6275 info@rodadeaco.com

Asia Pacific

AMOT - China Tel +86 21 6279 7700 Fax +86 21 5237 8560 shanghai@amot.com

AMOT - Singapore Tel +65 6408 6265 Fax +65 6293 3307 singapore@amot.com

Europe, Middle East and Africa

Chalwyn - England Tel +44 (0) 1284 715739 Fax +44 (0) 1284 760256 sales@chalwyn.com

AMOT - Germany Tel +49 (0) 40 8537 1298 Fax +49 (0) 40 8537 1331 germany@amot.com

www.chalwyn.com