

TRIESTE surface-mounted downlight CC

- dimmable downlight series, consisting of surface-mounted luminaires
- puristic design in matt signal white in rectangular form
- ideal for interior illumination in hotels, restaurants, bars or public buildings
- numerous configuration options for individual requirements



LIGHT DATA

	62408515	62408526	62408527	62408533	62408615	62408626	62408627	62408633
Color of body	weiß							
Typ. color temperature	5700 K	4000 K	2700 K	3000 K	5700 K	4000 K	2700 K	3000 K
Light color	daylight	cold white	warm white	white	daylight	cold white	warm white	white
Typ. luminous flux	900 lm~1215 lm		840 lm~1134 lm		900 lm~1215 lm		840 lm~1134 lm	
Efficiency	110 lm/W		103 lm/W		110 lm/W		103 lm/W	
Energy efficiency class	A+							
Typ. color rendering index	83							
SDCM MacAdam	3							
Beam angle	15 °				24 °			
Remarks	dimmable							
	62408715	62408726	62408727	62408733	62408815	62408826	62408827	62408833
Color of body	weiß							
Typ. color temperature	5700 K	4000 K	2700 K	3000 K	5700 K	4000 K	2700 K	3000 K
Light color	daylight	cold white	warm white	white	daylight	cold white	warm white	white
Typ. luminous flux	900 lm~1215 lm		840 lm~1134 lm		900 lm~1215 lm		840 lm~1134 lm	
Efficiency	110 lm/W		103 lm/W		110 lm/W		103 lm/W	
Energy efficiency class	A+							
Typ. color rendering index	83							
SDCM MacAdam	3							
Beam angle	38 °				60 °			
Remarks	dimmable							

POWER DATA

	62408515	62408526	62408527	62408533	62408615	62408626	62408627	62408633
Constant current range	0,35 mA~0,6 mA							
Typ. power	11 W							
LED type	CREE CXA 1507							
	62408715	62408726	62408727	62408733	62408815	62408826	62408827	62408833
Constant current range	0,35 mA~0,6 mA							
Typ. power	11 W							
LED type	CREE CXA 1507							

FURTHER DATA

	62408515	62408526	62408527	62408533	62408615	62408626	62408627	62408633
Length	80 mm							
Width	80 mm							
Height	95 mm							
Type of protection	IP 40							
Cable length	300 mm							
Connection	Connector							
Max. temperature Tc	75 ° C							
Max. ambient temperature Ta	40 ° C							
	62408715	62408726	62408727	62408733	62408815	62408826	62408827	62408833
Length	80 mm							
Width	80 mm							
Height	95 mm							
Type of protection	IP 40							
Cable length	300 mm							
Connection	Connector							
Max. temperature Tc	75 ° C							
Max. ambient temperature Ta	40 ° C							

DIMENSIONED DRAWING

