



1-888-677-5054 ****BUSINESS TO BUSINESS ONLY****
Call for Live Order Assistance & Technical Support (7:30am-5pm CST)

Categories > Couplings & Adapters > Dry Break Couplings & Adapters > Kamvalok Dry Break Couplings & Adapters> Kamvalok® Dry Break Coupling:: 3" Aluminum / Plated Steel



[VIEW CATALOG PAGE E0330](#)



Kamvalok® Dry Break Coupling

3" Aluminum / Plated Steel

These camlock couplings are the standard of the industry. The unique poppet design provides automatic closure in both the coupler & adapter to minimize spillage when disconnecting.

Coupler end also includes safety shut-off valve.

- Camlock by FPT ends.
- Transport series (1712ES) includes 2" elbow swivel with FPT port.
- Standard with aluminum bodies, plated steel internals, plated steel trim & Viton® seals (stainless bodies & other seals available).
- Liquid loss is approximately one cup each end.

[Add to Cart](#)

Part No.	Description	Wt.	Mfg.	Price	Qty.	Status	Pkg. Discount
OP1712D-AL30	Kamvalok Dry Break Camlock/Cam Lever Coupling, 3" Aluminum / Plated Steel	11.50 lbs.	OPW Engineered Systems	\$1,011.00	<input type="text"/>	Expected to ship Between 11/9 & 11/22	

[Add to Cart](#)

Notes:

Dry disconnects close when camlock is opened even if valve is left open.
Dust caps, plugs and replacement gaskets are also available.

Additional Information

Viton® is a registered trademark of DuPont Performance Elastomers

Related Items



OPW Engineered Systems Parts > Camlock / Cam Lever Coupling & Adapter Repair Kits



OPW Engineered Systems Parts > All OPW Repair Parts

Repair Parts

OPW Engineered Systems Repair Parts

© COPYRIGHT DULTMEIER SALES. ALL RIGHTS RESERVED